



The imageRUNNER 2206/2006 Series comprises of three models, iR2206N and 2006N (standard models) and iR2206 (entry model). imageRUNNER 2206N, 2006N support secure printing and Printer Command Language (PCL), and aim to improve convenience through the Send Lite function. The entry model is robust with basic functions, while the standard models support Wi-Fi and mobile printing by the use of CANON PRINT Business, Mopria, Google Cloud Print and more. These models boast improved durability and reliability in harsh environments, such as under conditions of high air





temperature and humidity.

TAKE CONTROL OF YOUR JOB OPERATIONS

- Touch Panel provides ease of use and reduces operational steps
- Customizable Home screen
- Improved screen visibility for Touch Panel with the use of backlight
- Up to 13 languages* supported

*Supports Malay, Thai, Vietnamese & more



COPY ID CARDS EFFORTLESSLY

- One-touch shortcut key makes copying of ID cards onto a single printout simple and efficient.
- Shortcut setup for ID card copy is not required

ENJOY MORE VALUE WITH imageRUNNER 2206N/2006N

((·)) WIRELESS LAN

Built-in with Wi-Fi capability, the imageRUNNER 2206N/2006N can connect wirelessly to a network via an access point. All other connected electronic devices on the same network will be able to print wirelessly, thereby providing greater convenience to users.





SECURE PRINTING

Protect confidential information from your documents by securing your print job with a configurable PIN.

Documents are held in the printer and released only when a PIN is entered. With the additional layer of verification, this eliminates security risks when printouts are left unattended. It also indirectly reduces paper wastage in the event of a misprint.



SEND LITE

- Scan to Email: Scan your original documents through the platen or automatic document feeder (ADF) and send the scanned document as an attachment to multiple email addresses.
- Scan to SMB: Scan your original documents through the platen or automatic document feeder (ADF) and store your files in the network folder via SMB protocol.
- Au-Send: Send function is available only to authenticated users, deterring various types of potential data leakages.



MOBILE PRINTING

- Supports businesses with mobile printing for a variety of file formats including image files, *PDF, *Microsoft Office files and web pages.
- Canon PRINT Business: Free download from App Store (iOS) and Google Play (Android)

SERIES LINE-UP

Model	Copy Speed	Network Print	Scan	Send Lite	WiFi	Dept ID	Platen Cover	DADF	Duplex	Max. Paper Cassette
iR2206N	22ppm	~	Push / Pull	Send to email/ SMB	~	~	Opt	Opt	Opt	2 x 250 sheets (80gsm)
iR2006N	20ppm	~	Push / Pull	Send to email/ SMB	~	~	Opt	Opt	Opt	2 x 250 sheets (80gsm)
iR2206	22ppm	×	Push / Pull	×	×	×	~	×	×	1 x 250 sheets (80gsm)

SPECIFICATIONS





GENERAL SPECIFICATIONS		iR2206	iR2006N	iR2206N				
Туре			nrome Multifunctional Device (Reader/Printer					
Copy/Print Speed	A4	22ppm	20ppm	22ppm				
	A3	11ppm	10ppm	11ppm				
Warm-Up Time (Time from device power on, until copy re	ady)		13 secs or less					
Recovery from sleep mode		4.3 secs						
First Copy Time (A4)		OF (MP	7.4 secs					
Memory Dimensions (W x D x H)		256 MB	512 MB 622 x 589 x 607mm (with ADF)					
Weight		622 x 589 x 502 622 x 589 x 607mm (with ADF) Approximately 28.7Kg Approximately 35.5 kg (with ADF)						
Installation Space (W × D)		920 x 589 mm (when multi purpose tray is extended)						
Power Supply		220 to 240 V AC, 50/60 Hz, 2.4 A	220 to 240 V AC,					
Max Power Consumption	Maximum Power Consumption:		1.5 kWh					
	When the machine is in the Sleep mode:	2 W						
Toner Yield (A4, 6% coverage)			Approx 10,200 sheets (A4, 6% coverage)					
Drum Yield		Approx 66,000 sheets	Approx 63,700 sheets	Approx 66,000 sheets				
PRINT SPECIFICATIONS								
Print Resolution		HEDRIT (C. I. I.)	600 x 600 dpi	D DCI / (O .:)				
Page Description Language(s) Print OS Compatibility		UFRII LT (Standard)	ws Server 2008/ 2008 R2/ 2012/ 2012 R2/ 20	1), PCL6 (Optional)				
	Naturada							
Interface	Network Others (Local Print/Scan)	N/A	Ethernet 100Base-Tx/10Base-T (IEEE 802. USB2.0 x 1	5 compliants, WEAN IEEE 602.11b/g/n				
Network Protocol	Onicis (Escarriniy scan)	N/A	TCP/ IP (IPv4/IPv6), USB ;Frame type: Ether / IPPS/ WSD/ Mopria/ Google Cloud Pri					
COPY SPECIFICATIONS								
Copy Resolution		600 x 600 dpi						
Multiple Copies/Prints Magnification			Up to 999 copies 25% - 400% (1% increment)					
SEND SPECIFICATIONS			2376 - 40076 (176 INCREMENT)					
Destination		N/A	Scan to Email (SMTP), ne	twork foldors (CMP)				
Scan Speed (Simplex, A4, 300 dpi)		N/A	BW: 13 sheets/ minute, 0					
Address Book		N/A	LDAP (5)/Local(104)					
SEND Resolution		N/A	BW/CL 300 x 300 dpi					
SEND File Format		N/A	PDF/ Compact PDF/ JPEG/ TIFF					
SCAN SPECIFICATIONS								
Destination	_	MF Scan Utility, application compatible with TWAIN/WIA						
Supported Protocol		TCP/ IP, USB						
Scan Speed (Simplex, A4, 300 dpi)		B\	BW: 23 sheets/ minute, CL: 12 sheets/ minute					
Scan Resolution		BW: 600 x 600 dpi, CL: 300 x 600 dpi TIFF/ JPEG/ PNG/ PDF (Compact, Searchable) / PDF (Divided into Single-Page Files)						
Scan File Format Scan OS Compatibility			vs Server2008/ 2008 R2/ 2012/ 2012 R2/ 201					
SECURITY		Willdows 10/ 8.17 7, Willdow	vs Server2006/ 2008 R2/ 2012/ 2012 R2/ 20	16, Mac O3 X 10.7.3 Of later				
Authentication		N/A	Department ID manage	amont (May 100 IDs)				
Network		IVA	Department ID management (Max: 100 IDs) Standard: IP/Mac Address Filtering, TLS Encrypted Communication, SNMP V3.0, IEEE 802.1X, IPv6, SMTP Authentication, POP Authentication before SMTP					
Network		N/A						
Document		N/A	Secure	Print				
PAPER HANDLING								
Paper Sizes	Casette 1	A3, B4	, A4R, A4, B5, B5R, A5R, India-LGL, FOOLSC					
	Cassette 2	-	A3, B4, A4R, A4,					
D 1 15 11 15 11 15	Multi Purpose Tray	A3, B4, A4R, A4, B5, B5R, A	5, A5R, India-LGL, FOOLSCAP, Envelope (CC	OM 10, Monarch, ISO-C5, DL)				
Paper Input Capacity (Standard)	Cassette 1		250 sheets (80gsm)					
Paper Input Capacity (Optional)	Multi Purpose Tray Cassette 2*	N/A	80 sheets (80gsm) 250 sheets	(80 gem)				
Paper Specification	Cassette 2"							
,	r Specification Cassette Multi Purpose Tray		Weight: 64 - 90gsm, Type: Plain (64 to 90gsm), Recycled (65 to 80gsm), Colour (64 to 80gsm), Pre-punched (75 to 80gsm) Weight: 60 - 128gsm; Type: Plain (64 to 90gsm), Heavy 1 (91 to 105gsm), Heavy 2 (106 to 128gsm), Recycled (65 to 80gsm), Colour (64 to 80gsm); Pre-punched (75 to 80gsm), Bond (75 to 90gsm), Transparency, Label, Envelope					
OPTIONAL ACCESSORIES DUPLEX AUTOMATIC DOCUMENT FEEDER - AY1*								
Type		N/A	Automatic Docu	ment Feeder				
Size of Originals		N/A	A3, B4, A4, A4R, B5, B5R, A5,					
Paper Weight		N/A	When scanning continuously: 52 to 105g/m2 When scanning a single original: 37 to 128g/m2					
Max. Number of Originals		N/A	50 sheets (A	· · · · · · · · · · · · · · · · · · ·				
Scanning Speed (Simplex)	Copying (A4 in BW at 600 dpi)	N/A	20 ipm	22 ipm				
	Scanning (A4 in BW 300 dpi)	N/A	23 i	pm				
Dimensions (W x D x H)		N/A	565 x 520.5					
Weight		N/A	Approximate	ely 7.0 kg				
OTHER OPTIONAL ACCESSORIES AND SUP	PLIES							
Duplex Unit-C1*, Platen Cover Type X*, Cassette Feeding *Available for iR2206N/2006N only.	Module – AD1*, FL Cassette-BB1*, Heater Kit-M2	2, Cassette Heater Unit-40, NPG-59 Drum Unit, NPG	G-59 Black Toner					

Canon Delighting You Always

Canon India Pvt. Ltd.

7th & 8th Floor, Tower B, Building #5, DLF Epitome Building, DLF Phase III, Gurugram-122002
Tel: 0124-4160000 | Fax: 0124-4160011 | www.canon.co.in

This document is for information purpose only and the contents are subject to change without notice. Product options, name and availability may vary by regions. Nothing in this document should be construed as a warranty. We expressly disclaim any liability or contractual obligations with respect to this document. Canon and Business Can Be Simple are trademarks of Canon Inc, and/or its affiliates. Other names may be the trademarks for their respective owners.

DEALER'S STAMP